

we deliver fresh air

Flexible Air Ducts & Accessories



afs.com.tr

AFS[®]



Class B - s1, d0
(EN 13501-1)
+
M1

ALUAFS.70

Duct Construction	: 3 ply aluminium 2 ply polyester
Nominal Thickness	: 70 micron
Diameter Range (Ø)	: 52 mm - 800 mm
Wire Spacing	: 35 mm (Ø ≥ 127 mm)
Temperature Range	: -30 °C / +150 °C
Air Velocity	: 30 m/s (max)
Operating Pressure	: 3000 Pa (max)
Standard Length	: 10 m
Packing	: Single cardboard box
Reaction to Fire	: Difficult to ignite
Certificates	: M1 (France) Class 1 (Italy) Class 0 (UK) Class B - s1, d0 (EN 13501-1)

EN ISO 11925-2
single flame source test report

EN ISO 13823
single burning item test report



All technical details on this leaflet are information purposes only and are subject to change without prior notice.

NYLON CLAMPS & PLIERS, TAPE

- Nylon clamps are specifically produced for all kinds of flexible air duct connections as an economical alternative.
- Nylon clamp edges are rounded to provide safer working environment.
- Self-locking system makes it easy and quick to apply.
- Nylon clamps can be reused
- Nylon clamps can be reused.
- Nylon clamp pliers are specifically produced for an easy application and tightening of Nylon Clamps.



TECHNICAL PROPERTIES

MATERIAL	NYLON 66		
	Application Range (mm)	W (mm)	L (mm)
	Ø 0 – 102	4.8	380
	Ø 0 – 140	7.6	530
	Ø 0 – 190	9.0	710
	Ø 0 – 229	9.0	800
	Ø 0 – 263	9.0	910
	Ø 0 – 360	9.0	1220

AFSTAPE	PLAIN 30 Micron	PLAIN 40 Micron	PLAIN 50 Micron	REINFORCED 125 Micron
Tensile Strength	37.5 N / 25 mm	50 N / 25 mm	70 N / 25 mm	120 N / 25 mm
Length	40 m	50 m	40 m	40 m
Service Temperature	-20°C / +120°C	-20°C / +120°C	-20°C / +120°C	-30°C / +80°C
Applying Temperature	+10°C / +40°C			
Standart Dimensions - width	48 mm, 72 mm, 96 mm			

PACKING

AFSTAPE Width	Box dimension cm x cm x cm		Pieces/box
48 mm	Plain	Reinforced	24
72 mm	25x25x30	29x29x30	16
96 mm			12



METAL CLAMPS



READY METAL CLAMPS

- Clamp Construction : AISI 430 Stainless Steel
 Locking Device Construction : Nickel plated housing, zinc plated screw
 Standard Length (Clamp) : 60/110 mm to 60/710 mm
 Clamp Width : 9 mm

READY METAL CLAMPS	Prati 60/110	Prati 60/135	Prati 60/145	Prati 60/170	Prati 60/215	Prati 60/270	Prati 60/325	Prati 60/380	Prati 60/425	Prati 60/525	Prati 60/660	Prati 60/710
LENGTH (mm)	370	450	476,5	549	560	705	890	1055	1235	1405	1685	2100



STRIP STEEL BANDING SYSTEM

- Clamp Construction : AISI 430 Stainless Steel
 Locking Device Construction : Nickel plated housing, zinc plated screw
 Packing (Clamp) : Single plastic cassette
 Quantity of Locking Devices : 50 pieces per box
 Standard Length (Clamp) : 30 m
 Clamp Width : 9 mm

look up 
certified energy
notice
the fresh air

